

## BROWDY AND NEIMARK, P.L.L.C.

ATTORNEYS AT LAW

## PATENT AND TRADEMARK CAUSES

SUITE 300

624 NINTH STREET, N.W.

WASHINGTON, D.C. 20001-5303

TELEPHONE (202) 628-5197

ALVIN BROWDY (1917-1998)

PATENT AGENT

ALLEN C. YUN, PH.D.

TELECOPIER FACSIMILE

(202) 737-3528

(202) 393-1012

E-MAIL

mail@browdyneimark.com

SHERIDAN NEIMARK  
ROGER L. BROWDYANNE M. KORNBAU  
NORMAN J. LATKER  
RONNI S. JILLIONS  
AOI NAWASHIROOF COUNSEL  
IVER P. COOPER  
JAY M. FINKELSTEINTELEFAX CONTROL SHEET

SENT TO:

Lee Wilson @ DTO  
(571) 273-4499

DATE SENT:

September 14, 2005

SUBJECT:

Missing page 7 in the application originally  
filed.

FROM:

Kim M. Durant, Issue Fee Clerk

Remarks:

9/14/05 Thank You!

## CONFIDENTIALITY NOTE

This confidential facsimile message is intended only for the individual entity named above, and may contain information that is privileged and exempt from disclosure under applicable law. If you, the reader of this message, are not the intended recipient, or the employee or agent responsible for delivering this message to the intended recipient, you are hereby notified that you should not copy this facsimile or distribute it to anyone other than the intended recipient. In addition, if you have received this telecopy in error, please immediately notify us by telephone or telefax and return the original message to us at the address above via the United States Postal Service. Finally, if it would not inconvenience you, we would appreciate it if you would fax this message to the intended recipient. Thank you.

If this transmission is not well received, please advise us at our telecopier no. 202-737-3528 or by e-mail at mail@browdyneimark.com, or call our voice telephone no. 202-628-5197.

-7-

*MARKE D UP*

*COPY*

*O.F.*  
*MISSING*  
*PAGE*

- Figure 7 is a half of a plan view of the foot of the jack.

- Figure 8 is an elevation or top view of Fig. 7.

- Figure 9 is a general view of the bar which is the object of the invention, with the variants concerning the shape of its cross section.

Looking now at Figure 1, we can appreciate a jack in which the support leg (1) and the vehicle support arm (2) are shown, connected by means of the threaded screw spindle (18) which is turned by the winding handle (19). The vehicle support arm (2) includes the vehicle support plate that receives the bodywork of the vehicle and pivots on the axis or shaft (20) in the support leg (1).

The support leg (1) has a foot (3) that turns on an axis (6) which is parallel to the other axis (20), while the position of the bar (23) that forms the auxiliary support can be observed in diagrammatic form.

In accordance with Figures 2 and 6 the end of the support leg (1) can be appreciated on the side near the foot (3), with its base and two holes (6) for placing the pivoting shaft of the said foot. The end has a quasi-triangular shape, as can be seen, and at the start of its base the tongue (7) is formed, with its hole (8), made out of the material of the base itself, forming the lower gap or cavity (8').

The elevation (22) that provides the lower cavity (21) in its central position can be seen, on which the downward protruding leg (10) is made and in turn has a hole that provides a gap (15).

As will be proven later, the bar that forms the auxiliary support passes through the hole (8) in the tongue (7) goes through the cavity (8') and passes through the lower cavity (21) and through the hole in the downward protruding leg (10).